



ARCHITECTURAL GUIDELINES

Southfork – Stage 3A *TAMANI COMMUNITIES*

RPL Lots Rear Lane R-1E

December 8, 2010

TAMANI COMMUNITIES

Southfork - Leduc

Rear Lane R1-E (RPL) Lots - Stage 3

Architectural Guidelines

DEVELOPER

Tamani Communities
#202, 3132 118 Avenue S.E.
Calgary, Alberta T2Z 3X1
Ph: (403) 723-8446 | Fax: (403) 212-0161
Laura Mills, Land Administrator

ARCHITECTURAL DESIGN CONSULTANT

Horizon Designs Ltd.
12816 52 Street
Edmonton, Alberta T5A 0B6
Ph: (780) 922-8004 | Fax: (780) 922-8013
horizondesigns@xplornet.com
May Molofy, Architectural Design Consultant

SURVEYOR

No mandated Surveyor. Any surveyor used must have ALS designation.
Under review

ENGINEER

Focus Engineering
#300, 9925 - 109 Street
Edmonton, Alberta T5K 2J8
Ph: (780) 466-6555 | Fax: (780) 463-0177
Allan Yamashita, P.Eng. , Senior Project Manager

Southfork - Leduc

ARCHITECTURAL GUIDELINES

REAR LANE RE-1 (RPL) LOTS

The information contained herein is provided as a guide to be used by builders/homeowners only. The Developer and its designated Architectural Design Consultant (ADC) make no warranties or representation as to the accuracy or completeness of these guidelines. Builders shall be fully and solely responsible for all designs, which follow these guidelines, and for the conformance to the appropriate building codes. These guidelines may be altered, amended, or varied by The Developer in its sole and absolute discretion.

OBJECTIVE

The Architectural Guideline is the mechanism which contributes to a high level of quality design in the community, thereby achieving the highest possible standard of visual appeal, benefiting the builder initially and the residents ultimately.

House plans will be reviewed in terms of the adherence to the design guidelines as detailed in this brochure. Certain modifications to house plans, elevations, and / or specifications may be requested where it is felt modifications are required to take advantage of unique lot characteristics or to conform to the overall objectives of the guidelines and the development on a lot by lot basis.

Applicants may provide alternative details to those outlined in these guidelines; however, they must demonstrate that conformity to the overall objectives for the quality of the area is being maintained. The acceptability of such alternatives is solely at the discretion of The Architectural Control Panel.

CONCEPT

Southfork is a master planned community located in south eastern Leduc, Alberta just off the Queen Elizabeth II Highway. Southfork boasts single detached, single rear lane and semi-detached front drive housing and Stage 3 will add an additional 255 lots to this area. Southfork boasts small town charm with access to City of Edmonton conveniences only a 15 minute drive away as well just as a short drive to the International Airport. Residents of Southfork have easy access to Leduc's established core of schools, emergency services, banking, shopping, theatre, and state of the art multipurpose recreational facility. Within the Leduc area there is also the William F. Leduc Regional Park and Telford Lake where families can enjoy canoeing and kayaking.

Each neighborhood will employ architectural guidelines to ensure that the COMTEMPORARY HERITAGE vision for this community is emulated. The goal in Southfork is to develop homes with architecture that draws on traditional architectural elements while addressing the needs of contemporary living and modern materials.

DISPUTES

Individual concerns will be presented by ADC to the The Architectural Control Panel – Developer to be adjudicated and

their decision will be final.

ARCHITECTURAL GUIDELINES

1) GENERAL DESIGN -

Builders will be encouraged to utilize the following guidelines in order to achieve and maintain comprehensive image throughout the community. Emphasis will be concentrated on trying to create a strong “curb appeal” to each home through attention to detail on the front entry.

2) ELEVATIONS / MODELS - Repetition

- a) The same house plan must be separated by 2 lots on the same side of the street (XAOX) and it will not be allowed directly across the street.
- b) This may be altered at the ADC discretion if it can be shown that the two houses in question are located so as not to be visible together from any given angle. While similar house plans and elevations are inevitable, it is possible to vary the design by changing the roof line design, and size and location of windows and doors etc. It is felt that adjacent houses can be altered to make it suitable.
- c) Revised elevations will be requested so that an accurate set of files can be kept for each lot.

3) COLORS

- a) Colors will be approved on a lot by lot basis. Primary wall colors will be approved on a lot by lot basis. Dark Bold contrasting colors are the central theme to emulate the Contemporary Heritage Home style.
- b) **SECONDARY COLORS** - each home is permitted to have one secondary color that is complementary to the main body color of the home. This color may be used on accent materials such as shakes or gable treatment. All secondary colors will be approved at the discretion of the ADC.
- c) **COLOR REPEITION** - cannot be repeated within 2 lots on the same side of the street (XAOX). The ADC has the authority to make changes in a color scheme, so that it blends with the adjacent homes. The ADC will make the final decision on the color of the houses. INTENSE SHADES will be reviewed on a lot by lot basis at the sole discretion of the ADC.
- d) **CORNERS @ front elevation** - are to be white in color
- e) **FRONT ENTRY DOOR** - must be painted in a contrasting deep/vibrant color or white.
- f) **TRIM** - must be white, including, window detail, shadow boards, porch columns, railing to punctuate contrasting darker siding colors.
- g) **FASCIA** - mandatory color - White
- h) **STONE OR BRICK** - selection cannot be repeated on adjacent lots (XOX)

4) MINIMUM HOUSE SIZES

- a) Square Footage's as per City of Leduc R-1E Residential land use bylaw

Bungalows and Bi-Levels	967.7 sq ft (not including bonus room)
1 ½ Storey	1,290.3 sq ft (not including bonus room)
2 Storeys	1,290.3 sq ft

Massing of the pocket is also required. IF the full pocket is not used the deviation cannot be more than **2 feet** of the pocket width.

- b) Minimum house sizes are established reviewed and may be amended from time to time by the Architectural Control Panel. Standards and approvals recognize the specific size, nature, and location of a site and the desire to avoid extremes.

Consideration is also given to optimizing sight lines and creating acceptable size transitions between adjacent homes and areas. Excessive total building height differences between adjacent dwellings will be reviewed on a lot by lot basis. Revisions may be required in order to reduce differences that are greater than 6-feet.

5) CORNER LOTS

- a) Special attention must be paid to side elevations and side yard setbacks on all corner lots.
- b) Side elevations facing a street are to be consistent in terms of design and detailing with front elevations. i.e.) window & door openings, roof lines etc. with visibility reviewed on a lot by lot basis.
- c) Two storey plans will be allowed on all corner lots.
- d) Construction of detached garage at time of construction of the dwelling is mandatory on corner lots with rear lane. Elevations to be submitted for review.

6) REAR ELEVATIONS

Any lot with high visibility i.e.) backing onto main roadway, **park**, greenbelt or school site requires additional detailing.

Rear Corners visible from roadway, park etc, must be white matching front elevation corner detail in color however may be 3" vs the wide required for the front.

Where rear fence is wood screen – second storey window & door openings require detailing
Where rear fence is chain link – ALL window & door openings require detailing.

7) SETBACKS / PARGE LINE / RISERS

- a) **SETBACK** - In addition to the City of Leduc's requirements for minimum setbacks, all houses should be built within the building envelope defined for each lot. However, builders may be required to adjust setback.

Houses should be placed perpendicular to the road, rather than angled on the lot, not parallel to one of the side property lines, whenever possible. The streetscape will flow more smoothly if the homes are positioned in a radial manner on curved roads. The line of houses on the street should follow the natural curve of the street.

b) **PARGE LINE** – No more than 24-inches allowed on elevations visible ahead of the fence tie-back line including entrances & any elevations facing a roadway i.e.) corner lot.

c) **RISERS AT ENTRANCE** - Due to City of Leduc Land Use Bylaw not allowing window wells, all measures are to be made to each individual house plan to keep risers at the entrance to a minimum.

No more than 4 exterior risers per set will be allowed at the front entrance, any further that may be required must be placed in the run of the walk or inside the entrance.

8) ELEVATION DETAILING - The amount of stone, wood trim, crezone panels, muttin bars, shutters, porches, or louvers used to provide interest and a sense of individuality while maintaining continuity to the streetscape will be consistent with the typical streetscape throughout the neighbourhood.

a) **FALSE FRONT** - material will not be permitted unless the material utilized on the front elevation of the dwelling is either brick or stone complete with minimum 24-inch wrap onto side elevation.

b) **EXTERIOR MATERIAL** – Vinyl siding or James Hardie Siding only (stucco exterior will not be permitted).

c) **SECONDARY WALL MATERIAL** may consist of cedar shakes, composite shakes, vinyl shakes, smart panel, board or batten detailing, stone or brick.

d) **WINDOW & DOOR OPENING DETAIL** - All front window and door openings require trim detail of full battens, top and bottom sills, or shutters.

e) **ENTRANCE COLUMNS** – to be simple line detail, corbelling at top or bottom or both allowed, narrow corner detailing acceptable. No double columns or in-lays allowed.

f) **FRONT ENTRY DOORS** - It is strongly suggested to use glass detail, however is not mandatory.

g) **BRICK OR STONE** – is not mandatory, however should it be used, it must be used in portions reflecting structural integrity. Where used must be minimum 3-feet in height on a wall surface, up to decking on veranda skirting. All stone or brick must wrap a minimum of 2-foot onto side elevations.

h) **RAILING** - acceptable materials, aluminum or painted or stained wood (natural pressure treated will not be allowed).

i) **WINDOW GRILLS OR MULLION** separation are optional, however if used must be used on all windows @ front elevation.

j) **CORNERS @ front elevation** - @ front elevation must be WIDE
May be vinyl, wood, or smart board. No metal clad corners will be allowed.

k) **FRONT PORCHES/VERANDAS** – are highly encouraged
– Contemporary Heritage homes are highly encouraged to incorporate a front porch – veranda on the front face of the home. Any such porch is to be substantial in depth, (minimum of 6 feet from the main face of the home.)

9) ROOFS

- a) **ROOF MATERIAL** - shall consist of asphalt shingles.
BP, Harmony-35 West Series, or IKO, Cambridge 30
- b) **ROOF COLOR** – mandatory color – black.
- c) **ROOF LINES** - are to be varied along the street through the use of varied designs such as hip, gable, dutch gable and cottage designs.
- d) **ROOF PITCH** - All main roof slopes will have a minimum 6/12 pitch where possible. (1st storey, 2 storey, garage & entry)
Lower slopes (allowed on verandas where roof line would interfere with 2nd storey windows.
Bungalows & Bi-levels to have steeper roof pitches in order to reduce the overall height difference with adjacent dwellings. Minimum 7/12 or steeper.
- e) **OVERHANGS** - are to be a minimum of 12-inch except over a cantilever, bay or boxed out window where the minimum overhang required is a 6" configuration.
- f) **FASCIA** - shall be minimum 8-inches
- g) **CHIMNEY** - All chimney flue or stacks that may be required must be boxed in with the same finish as the main body of the home.

10) GARAGES and DRIVEWAYS

- a) **PARKING** – All Rear Lane Access Lots
- b) **REAR DETACHED GARAGE** - When constructed, accessory buildings are to conform to the main building in terms of color, style and materials, minimum roof pitches, window & door detail.

If a rear detached garage is not built concurrently with the dwelling a two-car compacted gravel pad framed by 4 X 4 treated wood is to be provided in each rear yard and shall be a minimum of 18 X 20 in area to be supplied by the builder.

Rear detached garages are mandatory on corner lots & are to be built concurrently with the dwelling.

- c) **SIDEWALKS** – are to be hard surface.

11) LANDSCAPING

- a) **SECURITY DEPOSIT** - It is highly suggested (but not mandatory) the Builder obtain a security deposit from the homeowners' to guarantee rear yard landscaping is completed within the year in order to obtain City of Leduc final grade approval in order to obtain a final inspection.
- b) **COMPLETION OF LANDSCAPING** - is to be within one year of occupancy.

- c) **FRONT YARD LANDSCAPING** - to fence tie-back line is the responsibility of The Builder
- d) **LANDSCAPE REQUIREMENTS** - ahead of the fence tie-back line be completed with the following requirements;
 - i) A minimum 6" of topsoil & natural Sod to the fence tie-back line. No synthetic sod will be accepted.
 - ii) Minimum of one (1) tree; Minimum tree size requirements at time of planting
 - 1.5" caliper if deciduous (leaf bearing) Caliper measurements are taken 12" up from ground cover.
 - 6' in height if coniferous (Spruce or Pine); Pyramid cedars and upright Junipers will not be accepted as coniferous trees.
 - iii) No FULL front yard, hard surface landscaping will be considered.
- e) **ACCESSORY BUILDINGS** - if constructed are to be of similar materials & colors as approved for the dwelling, where possible are to be placed out of view line from any commuter roadway, park, etc.

12) **FENCING**

- a) It is the responsibility of the Builder to inform the Homeowner that it is their full responsibility to maintain any fence installed by the developer.
- b) Any interior fencing is to be overlap board wood screen, standard wood screen, built as per diagrams provided by The Developer. No chain link fencing will be allowed.
- c) Mandatory color – white throughout the neighborhood, including interior fence & tie-back fence.

13) **RETAINING STRUCTURES**

Builder/Homeowner is responsible for any retaining walls or wing walls that may be required as shown on final plot plan or otherwise.

14) **DOWNSPOUTS**

Must be directed away from the house, to streets or rear lanes.

Storm water must not be directed onto adjacent lots.

15) **SIGNAGE -**

Signage will be allowed on builder's lot only.

16) EXCAVATION MATERIAL

Builders must ensure that all excavation is kept within the confines of their lot. Any spillage on a road, sidewalk, or neighboring lot must be removed immediately or The Developer will arrange for its removal and invoice for expenses.

Clean Up - Builders/homeowners should encourage timely removal by all subtrades of litter on building sites. Failure to comply will result in a clean-up bill being charged to the lot. Supply of bins by the builder is MANDATORY. Any general clean up of the subdivision implemented by The Developer can, and will be charged prorated to all builders.

17) LOT GRADING

Lot grading is to follow the natural slope of the land form and is to be consistent with the Subdivision Grading Plan (which will be provided by The Developer). The minimum slope allowed is 2%. The Surveyor will prepare all plot plans. The staking out of the home will be jointly carried out by the builder and Surveyor. This procedure will facilitate establishing building elevations that are appropriate for the on-site grading conditions.

The Developer reserves the right to adjust the grading requirements between units after plans for affected homes have both been submitted. A coordinated grading review will be carried out by the Surveyor to ensure that the proposed final grades of a particular house do not adversely affect the adjacent house. The final grading requirements will be balanced by the Surveyor to the mutual benefit of both houses. It is the responsibility of the Purchaser, after final grading is complete, to provide to the Developer an approved Lot Grading Inspection from the City of Leduc that certifies compliance of the actual finished grades with the Approved Grading Plan.

Side-yard Grading: In addition to the critical grade control points at the corner pins of the lots, the grade elevations along the entire length of side property lines will also be important considerations.

All other guidelines contained herein are to be followed.

Conformity with these guidelines does not supersede the required approval process by The City of Leduc.

18) SECURITY DEPOSIT

A letter of credit deposit will be held by The Developer to cover all lots in this phase. Damages or infractions will be invoiced on a per lot basis by The Developer to The Builder for the following violations thereof, may retain the deposit or a portion:

Contravention of architectural objectives.

Damage to:

Curb stop – water service valve
Sidewalks, curbs and gutter
Asphalt
Boulevard landscaping and trees
Light standards
Fire hydrants

Catholic protection points
Grading and drainage swales
Any Developer provided improvement
Fencing

Security Deposit Return

Exterior completed

Rough grade completed

Water valve exposed and marked

Sidewalks and curbs cleaned

There will be a fee for re-inspection

DAMAGES

Cost of repairs due to builder damages to existing features and utilities will be billed to The Builder or deducted from The Builder's security deposit and builder will be invoiced for damages beyond what the security deposit covers.

Builders are encouraged to offer their customers a choice of colors and materials on any lot prior to application. Once approval has been made, changes will be discouraged to limit conflict with neighbors.

Should changes be necessary, they must be approved in writing by the coordinator prior to proceeding.

19) ARCHITECTURAL APPROVAL PROCESS

- a) Before applying for a Development or Building Permit, the applicant shall submit the following package for review to Horizon Designs Ltd.
 - One complete set of house plans.
 - Plot plan, prepared by designated surveyor, showing lot house grades and drainage pattern, floor and garage elevations and number of risers.
 - Horizon color application form complete with material, specific manufacturer, product names, & product codes.
- b) Horizon Designs Ltd. will review the plan and recommend approval, modification, or rejection of the application based on the adherence of the plans to these Guidelines within 7 business days from submission of complete application (circumstances permitting).

Once approved, Horizon Designs Ltd. will send the application review comments requesting revisions as required.

Revised plans & colors are required to be submitted in writing prior to final approval being granted.

After approval, the plans may not be altered without prior approval of Horizon Designs Ltd.

Approval of any and all house plans will be at the sole and unfettered discretion of the Developer.

- c) Should disputes arise, the Developer shall make the final decision on the acceptability of plans.
- d) A stake out date cannot be booked without final architectural approval.

20) IMPORTANT NOTES

- a) **CITY REGULATION** - Issuance of plot plan in no way absolves builders from compliance with all City and Provincial statutes

- b) **START** - Site work must NOT commence prior to Architectural Approval being granted and land agreements fully executed with The Developer.
- c) **INTERIM BUILDING REVIEW** - The Developer &/or the ADC may carry out an onsite review of the homes during construction. Periodic checks made to ensure conformance to approved grading plans and the Design Guidelines. Modifications may be requested related to actual site conditions.
- d) **PRE-INSPECTION** - Builder must pre-inspect their lot for damages to services, walks or curbs and list any damages in writing to The Developer.
- e) **ENGINEERING DRAWINGS** - Builders must check engineering drawings and the lot to assure that nothing obstructs driveways.
- f) **DISCRETION** - Notwithstanding anything else set out in these guidelines, Tamani Communities and the ADC may apply their respective judgements when considering and approving anything regulated or controlled by these guidelines. In so doing, the Developer and its consultants may provide waivers of or relaxations to any matter set out in these guidelines in their sole and absolute unfettered discretion.

In case of disagreement, Tamani Communities will render a final decision

No Right to Enforce - Only the developers may enforce the guidelines, no purchaser of a lot in this area may enforce these guidelines.

Right to Amend - The Developer may from time to time amend these guidelines as it sees fit in its sole and absolute unfettered discretion.

21) FORMS

Following are attached:

Pre-construction lot inspection form

Fencing details

Current version of the following may be obtained from Horizon Designs upon request.

Color application form

Final inspection request

July 13, 2010, guidelines finalized.

Nov. 16, 2010, rear corners backing onto roadway, park, etc must be white

10 (d) - garage overhead door to eave line detail

8-c, added brick/stone as a secondary material option

8-e, entrance columns

Dec. 8, 2010 - Page 6, Item 8-k - revised from "should have" to "are highly encouraged to have"

PRE-CONSTRUCTION LOT INSPECTION REPORT

DEVELOPER – TAMANI COMMUNITIES

Date of Inspection: _____

Subdivision: - Southfork Stage: 3A

Lot: _____ Block: _____ Plan: _____

Municipal Address: _____

Purchaser: _____


Item	Damaged		Description
	Yes	No	
Sidewalk			
Curb			
Driveway Apron			
Service Valve			
Swale			
Fence			
Other			

It is the Purchaser's responsibility to inspect all of the above items prior to stake-out. Snow, mud or other conditions do not release the Purchaser from this responsibility.

Signature

Date

IF THIS FORM IS NOT RECEIVED PRIOR TO CONSTRUCTION, THEN THE PURCHASER WILL BE LIABLE FOR THE COST OF REPAIRS WHICH WILL BE DETERMINED AT THE TIME OF THE FINAL INSPECTION.





14/03/2010 06:12 - Southfork - Southfork 2.0 (Landscape) Construction Drawing/Detail for Homeon Day 07/12/09A - Wood Screen Fence Detail.dwg

REVISIONS	
Date	Details

WOOD SCREEN FENCE DETAIL


Approved: S.L.
 Checked: S.L. & B.R.
 Date: JULY 2010 Scale: N.T.S. Drawn: T.M.


 DWG. NO.
FE.02A
FOCUS LANDSCAPE ARCHITECTURE




N:\030100572 - Southfork 2010\landscape\030100572-1-300\drawings\construction\Drawings\Details for Herten Design\FE.02A - Wood Screen Fence Detail.dwg

REVISIONS		WOOD SCREEN FENCE DETAIL		
Date	Details			
		Approved: S.L.		DWG. NO.
		Checked: S.L. & B.R.		FE.02A
		Date: JULY 2010	Scale: N.T.S.	Drawn: T.M.



- NOTES:**
- ◆ SPECIFICATIONS: ALL COMPONENTS AND WORKMANSHIP TO CONFORM TO THE CITY OF LEDUC LANDSCAPE DESIGN & CONSTRUCTION STANDARDS.
 - ◆ POSTS, BRACES AND RAILS - HOT DIPPED GALVANIZED WELDED STEEL PIPE, STANDARD WEIGHT (SCHEDULE 40, ASTM A120), ZINC COATED AT MINIMUM 566g/m.
 - ◆ CHAINLINK: 60mm MESH, 3.5m THICK WIRE, CLASS A ZINC COATED, GRADE 1 AT MINIMUM 490 g/m².
 - ◆ PIPE BRACES: GATE UP TO 1800mm WIDE - HORIZONTAL BRACE ONLY.
 - ◆ CHAIN LINK FENCE GATE TO BE BLACK VINYL COATED CHAIN LINK FABRIC, ON POWDER-COATED FRAMEWORK.
 - ◆ ALL DIMENSIONS ARE IN MILLIMETERS.

REVISIONS		CHAIN LINK FENCE SINGLE GATE DETAIL	 Engineering • Consulting • Planning
Date	Details		
		Approved: S.L.	DWG. NO.
		Checked: S.L. & B.R.	FE.04
		Date: JULY 2010 Scale: N.T.S. Drawn: T.M.	FOCUS LANDSCAPE ARCHITECTURE

N:\0\20100572 - Southfork 2010\landscape\021010027 2-1 300D\revis\Construction Dimension\Details for Horton Design\FE.04 - Chain Link Single Gate Detail.dwg

